




KS-6800 Series

6815 / 6812 **Fan-free**



SD-800

MSR (1/2/3), RFID (Option)



PD-309

Two - line LCD display with 20 characters per line (Gen6)



PD-310

Two - line LCD display with 20 characters per line

Features

- Fan free structure for harsh environment
- Spill proof water resistant structure allowing easy cleaning
- DDR2 SODIMM memory can extend to 2 GB
- Support Win XP Pro, POSReady, WEPOS and Linux environment
- 12" or 15" TFT active matrix LCD panel with 1024 x 768 resolution
- Supports SSD (Solid-State Drive) Data Storage Device
- Data storage device: 2.5" SATA HDD or optional CF card reader
- Optional RAID function for KS-6815 with supports of:
RAID 1 (Disk Mirroring); 2 x SATA I or SATA II HDD
Management software via SteelVine Manager
SMTP e-mail notification



CR-4000

"Screwless" tamper resistant design that cushions the drawer and protects the system



AURA-6800

High Speed (150mm/sec), low noise compact thermal printer

| Specification | KS-6812 | KS-6815 |
|--------------------------|--|--|
| Processor | Intel Atom CPU, N270 1.6G | |
| VGA Interface | D-SUB | |
| VGA Memory | Share system memory up to 128MB | |
| LCD Display | 12" 1024 X 768 | 15" 1024 X 768 |
| DRAM Memory | DDR-2 400/533MHz, 2 X SO-DIMM, Max. 2 GB | |
| Serial Port | 3 X, DB9 X 2, RJ-45 X 1 (RJ-45 to DB9 Cable Option) | |
| Parallel Port | N/A | Yes, proprietary port connector-Cable option |
| CF Card Slot | Option | |
| CR Port | Yes, one connector control 2 Cash Drawer | |
| Standard USB Port | 6 X, (4 X ports on the I/O plate, 2 X port on left side) | |
| Audio Port | Line-Out | N/A |
| Ethernet Port | 10 / 100 / 1000 Mb | |
| UPS Port | N/A | Yes |
| Touch Controller | USB interface | |
| Touch Sensor | 5 wires | |
| Wireless LAN | Option | |
| Storage Device | 2.5" SATA HDD or SSD HDD | |
| Power ON Wake Up | Through Alarm / LAN / Modem | |
| Mechanical Installation | Desk Top or Wall mount | |
| Power Saving | Suspension mode | |
| Indicator LED | Bi-color LED indicators | |
| Brightness Control | By push switch | |
| Dimension (WXDXH) | 309.9 X 262.3 X 288mm (12.2" X 10.3" X 11.3") | 378 X 304 X 364mm (12.5" X 12.0" X 14.3") |
| Weight (N. W.) | 4.1 kg | 7.7 kg |
| Fanfree System | Yes | |
| Speaker Build In | 2W speaker in main unit | |
| OS Support | POSReady, WEPOS, XP pro, Linux | |
| Option Peripheral | | |
| RAID Function | N/A | RAID 1 (Disk Mirroring) |
| MSR | SD-500: 2/3 tracks modular on Right Side of LCD panel | SD-400 / SD-400Z: MSR and/or Finger print sensor SD-800: MSR (1/2/3), RFID (option) |
| Wireless LAN | 802.11 b/g with USB interface | |
| CF Card Slot | Type II, memory card only | |
| Customer Pole Display | PD-2605: VFD pole display PD-309: LCD pole display | PD-2605: VFD pole display (Gen6) PD-2604: VFD pole display PD-2602: VFD pole display (Gen5) PD-310U: LCD pole display (USB interface) PD-309: LCD pole display (Gen6) PD-306: LCD pole display (Gen5) |
| 2nd LCD Display | N/A | 12" LM-6101B; 15" LM-6501B, VGA Port |
| 2nd HDD | N/A | Yes |
| SSD Storage Device | Support S-ATA I (150MB/s, 8G) | |
| UPS Battery | N/A | 2.3 Ahr / 12V |

❖ The product information and specifications are subject to change without prior notice.

